


DECLARATION OF PERFORMANCE

No: SVL-016E

1. Identification code of the produce type:	N2XY / YXV
2. Intended use or uses of the construction product , in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke
3. Registered trade name and Manufacturer address:	SEVAL KABLO AYD. CİH. İTH. İHR. SAN. TİC. A.Ş Hacıyüplü mah. 3119 sok. no: 5 Merkezefendi DENİZLİ/ TURKEY E: qc@sevalkablo.com W: www.sevalkablo.com
4. Notified Body,Code,Harmonized standard:	TURKISH STANDARDS INSTITUTION (TSE) NB No. 1783 EN 50575:2014+A1:2016
5. System or systems of assessment and verification of constancy of performance :	System 3
6. Declared Performance :	E _{ca}
7.Dangerous substances :	NPD
The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.	

Signed for and behalf of the manufacturer by
MAR 2017 DENİZLİ/TURKEY

Murat KAÇAMAZ
Plant Manager



DECLARATION OF PERFORMANCE

Scope of the Document

No: SVL-016E

CABLE TYPE: N2XY

VOLTAGE: 0.6/1 kV

CONSTRUCTION: Cu/XLPE/PVC/PVC

Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area
1	1.5mm ²	2	1.5mm ²	3	1.5mm ²
1	2.5mm ²	2	2.5mm ²	3	2.5mm ²
1	4mm ²	2	4mm ²	3	4mm ²
1	6mm ²	2	6mm ²	3	6mm ²
1	10mm ²	2	10mm ²	3	10mm ²
1	16mm ²	2	16mm ²	3	16mm ²
1	25mm ²	2	25mm ²	3	25mm ²
1	35mm ²			3	35mm ²
1	50mm ²			3	50mm ²
1	70mm ²			3	70mm ²
1	95mm ²			3	95mm ²
1	120mm ²			3	120mm ²
1	150mm ²			3	150mm ²
1	185mm ²			3	185mm ²
1	240mm ²			3	240mm ²
				3	300mm ²

Signed for and behalf of the manufacturer by
MAR 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager



DECLARATION OF PERFORMANCE

Scope of the Document

No:SVL-016E

CABLE TYPE: N2XY
VOLTAGE: 0.6/1 kV
CONSTRUCTION: Cu/XLPE/PVC/PVC

Number Of Cores	Cross-Sectional Area
4	1.5mm ²
4	2.5mm ²
4	4mm ²
4	6mm ²
4	10mm ²
4	16mm ²
4	25mm ²
4	35mm ²
4	50mm ²
4	70mm ²
4	95mm ²
4	120mm ²
4	150mm ²
4	185mm ²
4	240mm ²

Signed for and behalf of the manufacturer by
MAR 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager

