

DECLARATION OF PERFORMANCE

No: SVL-042E

1. Identification code of the produce type:	N2XBY
2. Intended use or uses of the construction product , in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke
3. Registered trade name and Manufacturer address:	SEVAL KABLO AYD. CİH. İTH. İHR. SAN. TİC. A.Ş Hacıyüplü mah. 3119 sok. no: 5 Merkezefendi DENİZLİ/ TURKEY E: qc@sevalkablo.com W: www.sevalkablo.com
4. Notified Body,Code,Harmonized standard:	TURKISH STANDARDS INSTITUTION (TSE) NB No. 1783 EN 50575:2014+A1:2016
5. System or systems of assessment and verification of constancy of performance :	System 3
6. Declared Performance :	E _{ca}
7.Dangerous substances :	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by
MAY 2017 DENİZLİ/TURKEY

Murat KAÇAMAZ
Plant Manager



DECLARATION OF PERFORMANCE

Scope of the Document

No: SVL-042E

CABLE TYPE: N2XBY

VOLTAGE: 0.6/1 kV

CONSTRUCTION: Cu/XLPE/PVC/GSTA/PVC

Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area
2	1.5mm ²	3	1.5mm ²	4	1.5mm ²
2	2.5mm ²	3	2.5mm ²	4	2.5mm ²
2	4mm ²	3	4mm ²	4	4mm ²
2	6mm ²	3	6mm ²	4	6mm ²
2	10mm ²	3	10mm ²	4	10mm ²
2	16mm ²	3	16mm ²	4	16mm ²
2	25mm ²	3	25mm ²	4	25mm ²
		3	35mm ²	4	35mm ²
		3	50mm ²	4	50mm ²
		3	70mm ²	4	70mm ²
		3	95mm ²	4	95mm ²
		3	120mm ²	4	120mm ²
		3	150mm ²	4	150mm ²
		3	185mm ²	4	185mm ²
		3	240mm ²	4	240mm ²

Signed for and behalf of the manufacturer by
MAY 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager



DECLARATION OF PERFORMANCE

Scope of the Document

No: SVL-042E

CABLE TYPE: N2XBY

VOLTAGE: 0.6/1 kV

CONSTRUCTION: Cu/XLPE/PVC/GSTA/PVC

Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area
5	1.5mm ²	3	16+10mm ²
5	2.5mm ²	3	25+16mm ²
5	4mm ²	3	35+16mm ²
5	6mm ²	3	50+25mm ²
5	10mm ²	3	70+35mm ²
5	16mm ²	3	95+50mm ²
5	25mm ²	3	120+70mm ²
		3	150+70mm ²
		3	185+95mm ²
		3	240+120mm ²

Signed for and behalf of the manufacturer by
MAY 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager