

DECLARATION OF PERFORMANCE

No: SVL-044E

1. Identification code of the produce type:	YY-SY
2. Intended use or uses of the construction product , in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke
3. Registered trade name and Manufacturer address:	SEVAL KABLO AYD. CİH. İTH. İHR. SAN. TİC. A.Ş Hacıyüplü mah. 3119 sok. no: 5 Merkezefendi DENİZLİ/ TURKEY E: qc@sevalkablo.com W: www.sevalkablo.com
4. Notified Body,Code,Harmonized standard:	TURKISH STANDARDS INSTITUTION (TSE) NB No. 1783 EN 50575:2014+A1:2016
5. System or systems of assessment and verification of constancy of performance :	System 3
6. Declared Performance :	E _{ca}
7.Dangerous substances :	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by
MAY 2017 DENİZLİ/TURKEY

Murat KAÇAMAZ
Plant Manager



DECLARATION OF PERFORMANCE

Scope of the Document

No: SVL-044E

CABLE TYPE: YY-SY

VOLTAGE: 300 / 500 V

CONSTRUCTION: Cu/PVC/PVC/GSWB/PVC

Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area
2	0.50mm ²	3	4mm ²	4	35mm ²
2	0.75mm ²	3	6mm ²	5	0.50mm ²
2	1mm ²	3	10mm ²	5	0.75mm ²
2	1.5mm ²	3	16mm ²	5	1mm ²
2	2.5mm ²	3	25mm ²	5	1.5mm ²
2	4mm ²	3	35mm ²	5	2.5mm ²
2	6mm ²	4	0.50mm ²	5	4mm ²
2	10mm ²	4	0.75mm ²	5	6mm ²
2	16mm ²	4	1mm ²	5	10mm ²
2	25mm ²	4	1.5mm ²	5	16mm ²
2	35mm ²	4	2.5mm ²	5	25mm ²
3	0.50mm ²	4	4mm ²	5	35mm ²
3	0.75mm ²	4	6mm ²	6	0.50mm ²
3	1mm ²	4	10mm ²	6	0.75mm ²
3	1.5mm ²	4	16mm ²	6	1mm ²
3	2.5mm ²	4	25mm ²	6	1.5mm ²

Signed for and behalf of the manufacturer by
MAY 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager

DECLARATION OF PERFORMANCE

Scope of the Document

No: SVL-044E

CABLE TYPE: YY-SY

VOLTAGE: 300 / 500 V

CONSTRUCTION: Cu/PVC/PVC/GSWB/PVC

Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area
6	2.5mm ²	8	2.5mm ²	19	1mm ²
6	4mm ²	12	0.50mm ²	19	1.5mm ²
6	6mm ²	12	0.75mm ²	19	2.5mm ²
7	0.50mm ²	12	1mm ²	25	0.50mm ²
7	0.75mm ²	12	1.5mm ²	25	0.75mm ²
7	1mm ²	12	2.5mm ²	25	1mm ²
7	1.5mm ²	12	4mm ²	25	1.5mm ²
7	2.5mm ²	12	6mm ²	25	2.5mm ²
7	4mm ²	15	0.75mm ²	27	0.50mm ²
7	6mm ²	18	0.50mm ²	27	0.75mm ²
7	10mm ²	18	0.75mm ²	27	1mm ²
7	16mm ²	18	1mm ²	27	1.5mm ²
8	0.50mm ²	18	1.5mm ²	27	2.5mm ²
8	0.75mm ²	18	2.5mm ²	30	0.50mm ²
8	1mm ²	19	0.50mm ²	30	0.75mm ²
8	1.5mm ²	19	0.75mm ²	30	1mm ²

Signed for and behalf of the manufacturer by
MAY 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager

DECLARATION OF PERFORMANCE

Scope of the Document

No: SVL-044E

CABLE TYPE: YY-SY

VOLTAGE: 300 / 500 V

CONSTRUCTION: Cu/PVC/PVC/GSWB/PVC

Number Of Cores	Cross-Sectional Area
30	1.5mm ²
30	2.5mm ²
34	0.50mm ²
34	0.75mm ²
34	1mm ²
34	1.5mm ²
34	2.5mm ²
36	0.50mm ²
36	0.75mm ²
36	1mm ²
36	1.5mm ²
36	2.5mm ²
41	1mm ²
50	1mm ²

Signed for and behalf of the manufacturer by
MAY 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager